

MARKED UP VERSION OF AMENDED CLAIMS

1. A method of investigating emissions from radioactive sources in an environment [(30)], the method comprising :-

providing an instrument, the instrument having a detector assembly, the detector assembly including a detector [(20; 46)] which generates a signal in response to a detected emission, the detector [(20; 46)] being provided with a greater level of shielding [(22; 42; 48; 900)] against emissions in one or more directions than in one or more other directions to define the field of view [(26; 904)] of the environment [(30)] **for the detector (20; 46);] for the detector;**

- introducing the detector assembly of the instrument into the environment [(30)]; characterised in that the method further comprises:-

providing the instrument with a moveable shielding component [(28; 52; 910)] which is moveable relative to the field of view [(26; 904)];

obtaining a signal count and/or count rate from the detector with at least a part of the [(30)] environment within the field of view [(26; 904)], the moveable shielding component [(28; 52; 910)] being out of the field of view [(26; 904)], the result forming the reference count and/or reference count rate for that given field of view [(26; 904)];

obtaining a signal count and/or count rate from the detector [(20; 46)] for the given field of view [(26; 904)], with a part [(32)] of the given field of view occluded by the moveable shielding component [(28; 52; 910)], the result forming the partially occluded view's count and/or count rate for that given field of view [(26; 904)] with that given part [(32)] occluded;

for a given occluded part [(32)] of a given field of view [(26; 904)], the reference count and partially occluded view count and/or reference count rate and partially occluded view count rate being considered against one another to provide information about the emissions arising from the given field of view [(26; 904)].

2. A method according to claim 1 which includes:-

obtaining a signal count and/or count rate from the detector [(20; 46)] with at least part of the environment [(30)] within the field of view [(26; 904)], the moveable shielding component [(28; 52; 910)] being out of the field of view;

moving at least part of the detector assembly to place at least another part of the environment [(30)] within the field of view [(26; 904)] and obtaining a signal count and/or count rate from the detector for that field of view [(26; 904)], the moveable shielding component [(28; 52; 910)] being out of that field of view;

considering the counts and/or count rates obtained for the two or more different fields of view [(26; 904)] and selecting one or more areas of the environment [(30)] for further investigation;

and then obtaining the signal count and/or count rate which result forms the reference count and/or reference count rate for that given field of view [(26; 904)] and the signal count and/or count rate which result forms the partially occluded view count and/or count rate for that given field of view [(26; 904)] with that given part [(32)] occluded.

3. A method according to claim 2 in which signal counts and/or count rates from the detector with at least part of the environment [(30)] within the field of view [(26)], the moveable shielding component [(28)] being out of the field of view, are obtained for sequential adjoining fields of view.
4. A method according to claim 2[or claim 3] in which the fields of view [(26)] are abutting or overlapping.
5. A method according to [any of claims 2 to 4] claim 2 in which the consideration of the counts and/or count rates obtained from two or more different fields of view [(26)] involves considering those fields of view [(26)] which have counts and/or count rates above a threshold level with those fields of view [(26)] having a count or count rate above the threshold level being selected.
6. A method according to [any one of claims 2 to 4] claim 2 in which the selected one or more areas of the environment [(30)] are further investigated by obtaining partially occluded view signal counts and/or count rates for a given field of view [(26)] with a plurality of different parts [(32)] of that given field of view [(26)] occluded.
7. A method according to claim 6 in which the method includes obtaining signal counts and/or count rates with each part [(32)] of the given field of view [(26)] occluded.
8. A method according to claim 6[or claim 7] in which different parts [(32)] of the field of view [(26)] are partially occluded by moving the moveable shielding component [(28)] within the field of view [(26)] of the detector [(20)] with the field of view [(26)] of the detector [(20)] fixed.
9. A method according to claim 1 in which signal counts and/or count rates from the detector [(20)] for the given field of view [(26)] are obtained with a plurality of different parts [(32)] of that given field of view [(26)] occluded by the moveable shielding component [(28)].

11. A method according to claim 9[or claim 10] in which different parts of the field of view are occluded by moving the moveable shielding component within the field of view of the detector, with the field of view of the detector fixed.
12. A method according to [any preceding] claim 1 in which the location (A, B) of the source or sources is determined in three dimensions.
13. A method according to claim 12 in which the location (A, B) is expressed in terms determined by the tilt and pan angles of the detector assembly and in terms of a distance from the detector [(20)] to the location (A, B).
14. A method according to [any preceding] claim 1 in which video camera or camera images of the environment are taken.
15. A method according to claim 14 in which the video camera or camera is mounted on the moveable shielding component [(28)].
16. A method according to [any preceding] claim 1 in which the detector [(46)] and detector shielding [(42)] are rotatably mounted about a first axis (Y-Y) and the moveable shielding component [(52)] is rotatably mounted about a second axis (X2-X2).
18. A method according to [any preceding] claim 1 in which the shielding includes a first generally planar component [(42)] and a second generally planar component [(42)] with a gap [(44)] between them, the gap [(44)], at least in part, defining the field of view.
19. A method according to [any preceding] claim 1 in which the shielding includes two opposing planar surfaces and two non-opposing non-planar surfaces, the opposing planar surfaces at least in part defining the field of view, the gap [(44)] between the opposing planar surfaces being closed by shielding [(48)] around part of the detector [(46)] to at least in part further define the field of view.
20. A method according to [any preceding] claim 1 in which the shielding [(42; 48)] defines a field of view having an angular extent of between 4.5° and 6° in one direction.
21. A method according to [any preceding] claim 1 in which the shielding [(42; 48)] defines a field of view with an angular extent of between 160° and 200° in a second direction.

22. A method according to **[any of claims 1 to 5]claim 1** in which the detector and detector shielding **[(900)]** are rotatably mounted about a first axis and a second axis and the moveable shielding component **[(910)]** is rotatably mounted about a first axis and a second axis.
24. A method according to **[any of claims 1 to 15 or 22 and 23]claim 1** in which the shielding **[(900)]** comprises a first conical portion and a second conical portion abutting the first conical portion.
26. A method according to **[any preceding] claim 1** in which the moveable shielding component **[(28; 52; 910)]** obscures between 5 and 10% of the field of view.
27. A method according to **[any preceding] claim 1** in which means for providing an optical image of the environment are provided on the moveable shielding component **[(28; 52; 910)]**.
28. A method according to **[any preceding] claim 1** in which the detector assembly is introduced into the environment by insertion through an aperture **[(704)]**, the aperture having a maximum diameter of less than 200mm.
29. A method according to **[any preceding] claim 1** in which the signal count and/or count rate for a field of view, with the moveable shielding component **[(28; 52; 910)]** out of the field of view is determined using a count period of less than 5 minutes.
30. A method according to **[any preceding] claim 1** in which different fields of view **[(26)]** are considered sequentially, moving from one field of view to an adjoining one.
31. A method according to **[any preceding] claim 1** in which the consideration involves considering those fields of view **[(26; 904)]** which produce high counts and/or count rates as being indicative of one or more sources being within those particular fields of view.
32. A method according to **[any preceding] claim 1** in which one or more areas may be selected for further investigation.
33. A method according to claim 32 in which the selection involves selecting one or more of the previously measured fields of view **[(26; 904)]** for use in the further investigation, the previously obtained count and/or count rate being used to form the reference count and/or count rate for the selected field of view **[(26; 904)]**.

34. A method according to claim 32 in which the selection includes the selection of one or more fields of view [(26; 904)] not corresponding to a previously measured field of view [(26; 904)], count and/or count rate from the detector for that field of view [(26; 904)] being obtained with the moveable shielding component [(28; 52; 910)] out of the field of view, that signal count and/or count rate forming the reference count and/or reference count rate for that selected field of view.

35. A method according to [any of claims 32 to 34] claim 32 in which partially occluded view signal counts and/or count rates are obtained for a given field of view [(26; 904)] with a plurality of different parts [(32)] of that given field of view [(26; 904)] occluded, the partially occluded view count and/or count rates for the plurality of different occluded views being considered together with the reference count and/or reference count rate for that given field of view [(26; 904)] to provide information about the emissions arising from that given field of view [(26; 904)].

36. A method according to [any preceding] claim 1 in which different partially occluded views are obtained by moving the moveable shielding component [(28; 52; 910)] within the field of view [(26; 904)] of the detector.

REMARKS

Applicant believes that all pending claims are allowable and respectfully requests a Notice of Allowance for this application from the Examiner. Should the Examiner believe that a telephone conference would expedite the prosecution of this application, the undersigned can be reached at the telephone number set out below.

Respectfully submitted,
BEYER WEAVER & THOMAS, LLP



Steve D. Beyer
Reg. No. 31,234

P.O. Box 778
Berkeley, CA 94704-0778
(650) 961-8300